

inline tensioned



Price list INLINE TENSIONED 2021

Valid from: 01.04.2021

Sprache/Language: Englisch



[INLINE TENSIONED Flex White T](#)

[INLINE TENSIONED Flex Grey T](#)

[INLINE TENSIONED Flex Micro T](#)

[INLINE TENSIONED Flex High Contrast T](#)

[INLINE TENSIONED Flex Rear T](#)

[Inline mounting](#)

[Modification](#)

[Controller](#)

Subject to modifications!
Prices in Euro, excl. VAT
Valid from: 01.04.2021
Version 04/2021

Detailed product information:
avstumpfl.com/de/projektionswaende/rollbildwaende/inline-tensioned/



System INLINE TENSIONED

[Product overview](#)

Roll-Up screen in a white (RAL9016) powder coated casing made of extruded aluminium profiles.

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.

The lateral, double-wired tensioning system is adjustable and guarantees a perfect flatness of the projection area.

This projection screen is produced according to the following safety and manufacturing regulations:

DIN 19045, DIN56950-4, DIN 4102 part 1, OENORM A 2115

INLINE TENSIONED with motor drive and projection surface FLEX WHITE T

INLINE Roll-Up screens are equipped with fast and noiseless tube motors (230 V),

with electromagnetically released disk brakes and overtemperature protection.

FLEX WHITE T is a pure white projection surface and optimized for a widest possible viewing angle, matt-white, Gain 1,2.

Format 16:9

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.

Material: FLEX WHITE T



Standard sizes - other sizes on request.

Discount Group (RM)

Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2C190136A/R5	INLINE 125 Tensioned, 16:9	190x136	180x101	81"	SK 12.5x12cm	18	26	1,802.00
BIT-2C210148A/R5	INLINE 125 Tensioned, 16:9	210x148	200x113	90"	SK 12.5x12cm	19	27	1,834.00
BIT-2C230159A/R5	INLINE 125 Tensioned, 16:9	230x159	220x124	100"	SK 12.5x12cm	20	28	1,866.00
BIT-2C250170A/R5	INLINE 125 Tensioned, 16:9	250x170	240x135	108"	SK 12.5x12cm	22	30	1,898.00
BIT-2C270181A/R5	INLINE 125 Tensioned, 16:9	270x181	260x146	117"	SK 12.5x12cm	25	33	1,930.00
BIT-2C290193A/R5	INLINE 125 Tensioned, 16:9	290x193	280x158	127"	SK 12.5x12cm	27	35	2,077.00
BIT-6C310204A/R5	INLINE 160 Tensioned, 16:9	310x204	300x169	136"	SK 16x16cm	37	57	3,420.00
BIT-6C360232A/R5	INLINE 160 Tensioned, 16:9	360x232	350x197	158"	SK 16x16cm	42	62	3,497.00
BIT-6C410260A/R5	INLINE 160 Tensioned, 16:9	410x260	400x225	181"	SK 16x16cm	47	67	3,939.00
BIT-6C450283A/R5	INLINE 160 Tensioned, 16:9	450x283	440x248	199"	SK 16x16cm	52	72	4,408.00

1)

1)

1)

Format 16:10

[back to the top](#)

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.

Material: FLEX WHITE T



Standard sizes - other sizes on request.

Discount Group (RM)

Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2W190148A/R5	INLINE 125 Tensioned, 16:10	190x148	180x113	84"	SK 12.5x12cm	18	26	1,813.00
BIT-2W210160A/R5	INLINE 125 Tensioned, 16:10	210x160	200x125	93"	SK 12.5x12cm	19	27	1,846.00
BIT-2W230173A/R5	INLINE 125 Tensioned, 16:10	230x173	220x138	102"	SK 12.5x12cm	21	29	1,880.00
BIT-2W250185A/R5	INLINE 125 Tensioned, 16:10	250x185	240x150	111"	SK 12.5x12cm	23	31	1,912.00
BIT-2W270197A/R5	INLINE 125 Tensioned, 16:10	270x197	260x162	121"	SK 12.5x12cm	26	33	1,976.00
BIT-2W290210A/R5	INLINE 125 Tensioned, 16:10	290x210	280x175	130"	SK 12.5x12cm	28	36	2,152.00
BIT-6W310223A/R5	INLINE 160 Tensioned, 16:10	310x223	300x188	139"	SK 16x16cm	38	58	3,438.00
BIT-6W360254A/R5	INLINE 160 Tensioned, 16:10	360x254	350x219	162"	SK 16x16cm	43	63	3,517.00
BIT-6W410285A/R5	INLINE 160 Tensioned, 16:10	410x285	400x250	186"	SK 16x16cm	48	68	4,077.00

1)

1)

BIT-6W450310A/R5	INLINE 160 Tensioned, 16:10	450x310	440x275	204"	SK 16x16cm	52	72	4,569.00	1)
------------------	-----------------------------	---------	---------	------	------------	----	----	----------	----

1) projection surface incl. one horizontal seam

[back to the top](#)

System INLINE TENSIONED

[Product overview](#)

Roll-Up screen in a white (RAL9016) powder coated casing made of extruded aluminium profiles.
Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
The lateral, double-wired tensioning system is adjustable and guarantees a perfect flatness of the projection area.

This projection screen is produced according to the following safety and manufacturing regulations:
DIN 19045, DIN56950-4, DIN 4102 part 1, OENORM A 2115

INLINE TENSIONED with motor drive and projection surface FLEX GREY T

INLINE Roll-Up screens are equipped with fast and noiseless tube motors (230 V),
with electromagnetically released disk brakes and overtemperature protection.

FLEX GREY T is a light gray projection surface for enhanced black levels in non-darkened projection environments, matt light gray, Gain 0,65.




Format 16:9

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
Material: FLEX GREY T



Standard sizes - other sizes on request.

Discount Group (RM)

Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2C190136B/R5	INLINE 125 Tensioned, 16:9	190x136	180x101	81"	SK 12.5x12cm	18	26	1,856.00
BIT-2C210148B/R5	INLINE 125 Tensioned, 16:9	210x148	200x113	90"	SK 12.5x12cm	19	27	1,889.00
BIT-2C230159B/R5	INLINE 125 Tensioned, 16:9	230x159	220x124	100"	SK 12.5x12cm	20	28	1,922.00
BIT-2C250170B/R5	INLINE 125 Tensioned, 16:9	250x170	240x135	108"	SK 12.5x12cm	22	30	1,955.00
BIT-2C270181B/R5	INLINE 125 Tensioned, 16:9	270x181	260x146	117"	SK 12.5x12cm	25	33	1,988.00
BIT-2C290193B/R5	INLINE 125 Tensioned, 16:9	290x193	280x158	127"	SK 12.5x12cm	27	35	2,139.00
BIT-6C310204B/R5	INLINE 160 Tensioned, 16:9	310x204	300x169	136"	SK 16x16cm	37	57	3,488.00
BIT-6C360232B/R5	INLINE 160 Tensioned, 16:9	360x232	350x197	158"	SK 16x16cm	42	62	3,567.00
BIT-6C410260B/R5	INLINE 160 Tensioned, 16:9	410x260	400x225	181"	SK 16x16cm	47	67	4,018.00
BIT-6C450283B/R5	INLINE 160 Tensioned, 16:9	450x283	440x248	199"	SK 16x16cm	52	72	4,496.00

Format 16:10




[back to the top](#)

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
Material: FLEX GREY T



Standard sizes - other sizes on request.

Discount Group (RM)

Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2W190148B/R5	INLINE 125 Tensioned, 16:10	190x148	180x113	84"	SK 12.5x12cm	18	26	1,868.00
BIT-2W210160B/R5	INLINE 125 Tensioned, 16:10	210x160	200x125	93"	SK 12.5x12cm	19	27	1,901.00
BIT-2W230173B/R5	INLINE 125 Tensioned, 16:10	230x173	220x138	102"	SK 12.5x12cm	21	29	1,936.00
BIT-2W250185B/R5	INLINE 125 Tensioned, 16:10	250x185	240x150	111"	SK 12.5x12cm	23	31	1,970.00
BIT-2W270197B/R5	INLINE 125 Tensioned, 16:10	270x197	260x162	121"	SK 12.5x12cm	26	33	2,035.00
BIT-2W290210B/R5	INLINE 125 Tensioned, 16:10	290x210	280x175	130"	SK 12.5x12cm	28	36	2,216.00
BIT-6W310223B/R5	INLINE 160 Tensioned, 16:10	310x223	300x188	139"	SK 16x16cm	38	58	3,506.00
BIT-6W360254B/R5	INLINE 160 Tensioned, 16:10	360x254	350x219	162"	SK 16x16cm	43	63	3,588.00
BIT-6W410285B/R5	INLINE 160 Tensioned, 16:10	410x285	400x250	186"	SK 16x16cm	48	68	4,159.00
BIT-6W450310B/R5	INLINE 160 Tensioned, 16:10	450x310	440x275	204"	SK 16x16cm	52	72	4,660.00

[back to the top](#)

1) projection surface incl. one horizontal seam

System INLINE TENSIONED

[Product overview](#)

Roll-Up screen in a white (RAL9016) powder coated casing made of extruded aluminium profiles.
 Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
 The lateral, double-wired tensioning system is adjustable and guarantees a perfect flatness of the projection area.

This projection screen is produced according to the following safety and manufacturing regulations:
 DIN 19045, DIN56950-4, DIN 4102 part 1, OENORM A 2115

INLINE TENSIONED with motor drive and projection surface FLEX MICRO T

INLINE Roll-Up screens are equipped with fast and noiseless tube motors (230 V),
 with electromagnetically released disk brakes and overtemperature protection.

FLEX MICRO T is a sound-permeable, matt-white projection surface. Micro perforation 6%, Gain 0,8.

Format 16:9

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.

Material: FLEX MICRO T

Standard sizes - other sizes on request.

Discount Group (RM)



Art. Nr.	Description	cm	cm	inch	Casing dimensions	kg net	kg gross	List Price in €
BIT-2C190136C/R5	INLINE 125 Tensioned, 16:9	190x136	180x101	81"	SK 12.5x12cm	18	26	2,252.00
BIT-2C210148C/R5	INLINE 125 Tensioned, 16:9	210x148	200x113	90"	SK 12.5x12cm	19	27	2,293.00
BIT-2C230159C/R5	INLINE 125 Tensioned, 16:9	230x159	220x124	100"	SK 12.5x12cm	20	28	2,333.00
BIT-2C250170C/R5	INLINE 125 Tensioned, 16:9	250x170	240x135	108"	SK 12.5x12cm	22	30	2,372.00
BIT-2C270181C/R5	INLINE 125 Tensioned, 16:9	270x181	260x146	117"	SK 12.5x12cm	25	33	2,412.00
BIT-2C290193C/R5	INLINE 125 Tensioned, 16:9	290x193	280x158	127"	SK 12.5x12cm	27	35	2,596.00
BIT-6C310204C/R5	INLINE 160 Tensioned, 16:9	310x204	300x169	136"	SK 16x16cm	37	57	3,762.00
BIT-6C360232C/R5	INLINE 160 Tensioned, 16:9	360x232	350x197	158"	SK 16x16cm	42	62	3,846.00

Format 16:10

[back to the top](#)

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.

Material: FLEX MICRO T

Standard sizes - other sizes on request.

Discount Group (RM)



Art. Nr.	Description	cm	cm	inch	Casing dimensions	kg net	kg gross	List Price in €
BIT-2W190148C/R5	INLINE 125 Tensioned, 16:10	190x148	180x113	84"	SK 12.5x12cm	18	26	2,266.00
BIT-2W210160C/R5	INLINE 125 Tensioned, 16:10	210x160	200x125	93"	SK 12.5x12cm	19	27	2,307.00
BIT-2W230173C/R5	INLINE 125 Tensioned, 16:10	230x173	220x138	102"	SK 12.5x12cm	21	29	2,349.00
BIT-2W250185C/R5	INLINE 125 Tensioned, 16:10	250x185	240x150	111"	SK 12.5x12cm	23	31	2,390.00
BIT-2W270197C/R5	INLINE 125 Tensioned, 16:10	270x197	260x162	121"	SK 12.5x12cm	26	33	2,470.00
BIT-2W290210C/R5	INLINE 125 Tensioned, 16:10	290x210	280x175	130"	SK 12.5x12cm	28	36	2,690.00
BIT-6W310223C/R5	INLINE 160 Tensioned, 16:10	310x223	300x188	139"	SK 16x16cm	38	58	3,781.00
BIT-6W360254C/R5	INLINE 160 Tensioned, 16:10	360x254	350x219	162"	SK 16x16cm	43	63	3,869.00

[back to the top](#)

System INLINE TENSIONED

[Product overview](#)

Roll-Up screen in a white (RAL9016) powder coated casing made of extruded aluminium profiles.
Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
The lateral, double-wired tensioning system is adjustable and guarantees a perfect flatness of the projection area.

This projection screen is produced according to the following safety and manufacturing regulations:
DIN 19045, DIN56950-4, DIN 4102 part 1, OENORM A 2115

INLINE TENSIONED with motor drive and projection surface FLEX HIGH CONTRAST T

INLINE Roll-Up screens are equipped with fast and noiseless tube motors (230 V),
with electromagnetically released disk brakes and overtemperature protection.

FLEX HIGH CONTRAST T is a silver gray projection surface for projections in slightly darkened rooms.
Optimized light distribution and improved black level, silver gray, Gain 1,2.




Format 16:9

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
Material: FLEX HIGH CONTRAST T

Standard sizes - other sizes on request.

Discount Group (RM)



Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2C190136D/R5	INLINE 125 Tensioned, 16:9	190x136	180x101	81"	SK 12.5x12cm	18	26	1,982.00
BIT-2C210148D/R5	INLINE 125 Tensioned, 16:9	210x148	200x113	90"	SK 12.5x12cm	19	27	2,018.00
BIT-2C230159D/R5	INLINE 125 Tensioned, 16:9	230x159	220x124	100"	SK 12.5x12cm	20	28	2,053.00
BIT-2C250170D/R5	INLINE 125 Tensioned, 16:9	250x170	240x135	108"	SK 12.5x12cm	22	30	2,088.00
BIT-2C270181D/R5	INLINE 125 Tensioned, 16:9	270x181	260x146	117"	SK 12.5x12cm	25	33	2,123.00
BIT-2C290193D/R5	INLINE 125 Tensioned, 16:9	290x193	280x158	127"	SK 12.5x12cm	27	35	2,285.00
BIT-6C310204D/R5	INLINE 160 Tensioned, 16:9	310x204	300x169	136"	SK 16x16cm	37	57	3,591.00

Format 16:10




[back to the top](#)

Surface area with a 5 cm black border and additional 30 cm black drop for increased subjective contrast.
Material: FLEX HIGH CONTRAST T

Standard sizes - other sizes on request.

Discount Group (RM)



Art. Nr.	Description				Casing dimensions	kg net	kg gross	List Price in €
BIT-2W190148D/R5	INLINE 125 Tensioned, 16:10	190x148	180x113	84"	SK 12.5x12cm	18	26	1,994.00
BIT-2W210160D/R5	INLINE 125 Tensioned, 16:10	210x160	200x125	93"	SK 12.5x12cm	19	27	2,030.00
BIT-2W230173D/R5	INLINE 125 Tensioned, 16:10	230x173	220x138	102"	SK 12.5x12cm	21	29	2,068.00
BIT-2W250185D/R5	INLINE 125 Tensioned, 16:10	250x185	240x150	111"	SK 12.5x12cm	23	31	2,104.00
BIT-2W270197D/R5	INLINE 125 Tensioned, 16:10	270x197	260x162	121"	SK 12.5x12cm	26	33	2,173.00
BIT-2W290210D/R5	INLINE 125 Tensioned, 16:10	290x210	280x175	130"	SK 12.5x12cm	28	36	2,367.00
BIT-6W310223D/R5	INLINE 160 Tensioned, 16:10	310x223	300x188	139"	SK 16x16cm	38	58	3,609.00

[back to the top](#)

System INLINE TENSIONED

[Product overview](#)

Roll-Up screen in a white (RAL9016) powder coated casing made of extruded aluminium profiles.

Surface area without black masking

The lateral, double-wired tensioning system is adjustable and guarantees a perfect flatness of the projection area.

This projection screen is produced according to the following safety and manufacturing regulations:

DIN 19045, DIN56950-4, DIN 4102 part 1, OENORM A 2115

INLINE TENSIONED with motor drive and projection surface FLEX REAR T

INLINE Roll-Up screens are equipped with fast and noiseless tube motors (230 V), with electromagnetically released disk brakes and overtemperature protection.

FLEX REAR T is a greyish green translucent rear projection surface

Wide viewing angle, projected light is diffused in all directions, Gain 1,32.

Discount Group (RM)

Prices on request



INLINE-Projection Screens for CEILING INTEGRATION

[Product overview](#)

All projection screens in system INLINE are available as projection screens for CEILING INTEGRATION.

The clip-brackets on either sides of the screen are stackable to allow convenient access to the screws for mounting and servicing.

Mounting and dismounting of the projection screen can be done without additional access!

The mounting frame modification for ceiling integration can be done in factory only.



Discount Group (RM)

Art. Nr.	Description	List Price in €
BRZ-EBR/125	Additional charge for INLINE 125	144.00
BRZ-EBR/160	Additional charge for INLINE 160	186.00

INLINE-Mounting Set for suspended ceiling

Thread rods (100 cm) enable a continuously adjustment to the ceiling level.



Discount Group (RM)

Art. Nr.	Description	List Price in €
BIZ-MSAD/125	Mounting-Set for INLINE 125	83.00
BIZ-MSAD/160	Mounting-Set for INLINE 160	102.00

INLINE - Mounting Systems

[back to the top](#)


For casing dimensions SK 12.5 x 12 cm and SK 16 x 16 cm.

Mounting-, ceiling-, wall- and wall/ceiling brackets are shipped in pairs!

INLINE 125 - QuickMount™ - standard mounting bracket

Standard delivery with mounting brackets for all wall- or ceiling mounting options - also for inaccessible areas.

Installation can be performed safely and easily by one person.



Discount Group (RM)

Art. Nr.	Description	List Price in € / Pair
BIZ-QM/125	QuickMount Mounting bracket for casing 12,5 x 12 cm	42.00

INLINE 160 - In-line standard mounting bracket

As a standard INLINE Roll-Up projection screens in casing 16 x 16 cm come with mounting brackets (for wall- or ceiling mounting).



Discount Group (RM)

Art. Nr.	Description	List Price in € / Pair
BIZ-MW/160	INLINE-Mounting bracket	26.00

INLINE 125 - ceiling mounting plate

Ceiling mounting plate for casing 12,5 x 12 cm.



Discount Group (RM)

Art. Nr.	Description	List Price in € / Pair
BIZ-DMP/090/125	Inline mounting plate for ceiling mounting	26.00

INLINE 125 - ceiling mounting plate incl. mounting set

Version of ceiling mounting plate for installation with a mounting set (thread rods 100 cm).

Discount Group (RM)

Art. Nr.	Description	List Price in € / Pair
----------	-------------	------------------------

BIZ-MSAD/DMP/090/125	Inline mounting plate incl. mounting set	83.00
----------------------	--	-------

INLINE 125 - Ceiling bracket

The INLINE-Ceiling bracket can be attached at any point on the case.
Continuous T-slots on the top provide maximum flexibility for mounting.



Discount Group (RM)

Art. Nr.	Description	List Price in €
BIZ-AHID2/125	INLINE-Ceiling bracket 20cm, casing SK 12.5x12cm	87.00
BIZ-AHID4/125	INLINE-Ceiling bracket 40cm, casing SK 12.5x12cm	93.00
BIZ-AHID6/125	INLINE-Ceiling bracket 60cm, casing SK 12.5x12cm	101.00
BIZ-AHIDX/125	INLINE-Ceiling bracket special (5-90cm) casing SK 12.5x12cm	101.00

INLINE 125 - Wall bracket

The INLINE-Wall bracket can be attached at any point on the case.
Continuous T-slots on the top provide maximum flexibility for mounting.



Discount Group (RM)

Art. Nr.	Description	List Price in €
BIZ-AHIW2/125	INLINE-Wall bracket 20cm, casing SK 12.5x12cm	87.00
BIZ-AHIW4/125	INLINE-Wall bracket 40cm, casing SK 12.5x12cm	93.00
BIZ-AHIW6/125	INLINE-Wall bracket 60cm, casing SK 12.5x12cm	101.00
BIZ-AHIWX/125	INLINE-Wall bracket special (5-60cm) SK 12.5x12cm	101.00

INLINE 160 - Wall/Ceiling bracket

The INLINE-Wall/Ceiling bracket can be used for wall or ceiling mounting because of it's horizontal and vertical mounting options.



Discount Group (RM)

Art. Nr.	Description	List Price in €
BIZ-AHWD2/160	INLINE-Wall/Ceiling bracket 20cm, SK 16x16cm	101.00
BIZ-AHWD4/160	INLINE-Wall/Ceiling bracket 40cm, SK 16x16cm	103.00
BIZ-AHWDX/160	INLINE-Wall/Ceiling bracket special (5-40cm) casing SK 16x16cm	103.00

The mentioned length refers to the distance between wall and rear panel of the case.

INLINE-Wall/Ceiling bracket 12,5 x 12 cm with reconstruction of side caps available on request.

Brackets in special lengths:

Length for BIZ-AHIDX/125 can be between 5cm (min.) and 90 cm (max.).

Length for BIZ-AHIWX/125 can be between 5cm (min.) and 60 cm (max.).

Length for BIZ-AHWDX/160 can be between 5 cm (min.) and 40 cm (max.).

Please specify the distance between wall and rear panel of case or ceiling and top panel of case, respectively on your order!

[back to the top](#)

**Casing in different Colour**[Product overview](#)**Discount Group (NN)**

Art. Nr.	Description		List Price in €
BRZ-C/I125	BASIC PRICE special varnish colour code RAL	for INLINE 125	190.00
BRZ-C/I125/FC	EXTRA CHARGE different colour code (NCS,...)	for INLINE 125	50.00
BRZ-C/I125/GG	EXTRA CHARGE different gloss level	for INLINE 125	40.00
BRZ-C/I125/SL	EXTRA CHARGE structured coating	for INLINE 125	50.00
BRZ-C/I160	BASIC PRICE special varnish colour code RAL	for INLINE 160	250.00
BRZ-C/I160/FC	EXTRA CHARGE different colour code (NCS,...)	for INLINE 160	60.00
BRZ-C/I160/GG	EXTRA CHARGE different gloss level	for INLINE 160	50.00
BRZ-C/I160/SL	EXTRA CHARGE structured coating	for INLINE 160	60.00

above 4m screen width: Bottom bar not varnished, instead coloured as masking black or without masking white
Please specify exact colour code on your order!

1):

Standard gloss level "6-antique" - please mention the required, different gloss level on your order!

Possible gloss levels: 1-high gloss, 2-gloss, 3-silk gloss, 4-satin, 5-silk matt, 6-antique, 7-antique matt, 8-matt, 9-dull matt

2):

Possible structured coatings: fine, medium, rough

Modifications for Roll-Up Projection Screens**Discount Group (RM)**

Art. Nr.	Description		List Price in €
BRZ-MOD/BH	Roll-Up modification	fabric unwinds to front side	31.00
BRZ-MOD/MR	Roll-Up modification	motor mounted right	31.00

Discount Group (RZ)

Art. Nr.	Description		List Price in €
BRZ-S-C-HIPRO05	Somfy HiPro-cable	5m, motor cable	32.00
BRZ-S-C-HIPRO10	Somfy HiPro-cable	10m, motor cable	42.00

[back to the top](#)